



T - 856-232-4700
F - 856-232-7533

1651 Sicklerville Rd.
Sicklerville NJ 08081
www.PreferredPartyPlace.com

Star 174SBA Broil-O-Dog Hot Dog Broiler GENERAL OPERATING PROCEDURES

1. Pre-heat unit for 15 minutes while set at 10.
2. Place the desired quantity of hot dogs on the holders. **NOTE:** A lower temp control setting may be used for slower broiling. The time required to broil the hot dogs will vary, depending upon the size and the temperature of the hot dogs when placed in the Broil-O-Dog.
3. Place the desired quantity of buns in the bun drawer For best results leave buns in the bag. A 50 watt warming elements is installed to keep buns warm.
4. Turn control to 6 or 7 to keep the hot dogs in a ready-to-serve condition. Hot dogs can be held for several hours on this unit without loss of flavor or shriveling.
5. Load or unload the hot dog wheel by pressing in and holding the serve switch to stop the hot dog wheel.

NOTE: When you turn the switch to the "OFF" position, you turn off the heating element.

COOKING

The heat control provides an infinite range of settings for a wide variety of hot dogs and installation conditions. The size, content and shape of the product and the installation of any sanitary food shields or sneeze guards will determine the proper heat setting. The National Sanitation Foundation requires that perishable foods be kept at 140°F or above during serving periods. The product should be kept refrigerated until ready for use. Cooking time will vary depending on the starting temperature and the qualities of the product.